



A401

**BAZOOKA SPOT
REMOVER**



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: BAZOOKA SPOT REMOVER **Product Code:** A401

Manufacturer: Prochem Europe Ltd., Oakcroft Road, Chessington, Surrey KT9 1RH, UK. Telephone No (office hours 8am to 5pm, Monday to Friday only): 020 8974 1515 (UK) +44 20 8974 1515 (EC) Chemical Product Manager E, H & S

Website: www.prochem.co.uk Email: sales@prochem.co.uk

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department, who may seek advice from the **UK National Poisons Information Service**, where our full product details are held.

Product Description & Directions For Use:

Bazooka Spot Remover is specially formulated for use with Prochem's Bazooka Gum Removal unit to effortlessly remove chewing gum from carpets. It can also be used without the Bazooka unit to remove chewing gum and many oil-based spots from carpets, fabrics and most surfaces.

Always pretest carpet, fabric or surface to be treated in a small inconspicuous area for colour fastness and texture change. Do not use this product on carpets or carpet tiles with heavy latex or bitumen backings.

Lightly spray Bazooka Spot Remover onto gum or spot and leave for 1 to 2 minutes. For best results, pierce chewing gum with Prochem perforator or fork to allow penetration. Scrape gum or spot residue with a blunt knife, or agitate with spotting brush or Bazooka power unit. For other spots such as grease and oil, blot treated area with clean white towel or tissue.

For difficult chewing gum deposits or spots, repeat process if required.

Finally, rinse area with damp sponge, prespotter or extraction machine to remove residues. Brush fibres to align pile and leave to dry.

SECTION 2: HAZARDS IDENTIFICATION

Classification: Extremely flammable. Repeated exposure may cause skin dryness or cracking.

Eye Contact: Contact with liquid or vapour may cause mild eye irritation.

Skin Contact: Prolonged or repeated contact may cause irritation.

Inhalation: Exposure to high concentrations of vapour may cause dizziness, headaches and nausea.

Ingestion: Unlikely in aerosol form. May cause irritation of the mouth, respiratory tract and intestinal system.

Environment: Contains orange terpenes which is classified as Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE	RISK (See Section 16)	EINECS NO.	CAS NO.	% W/W (EC RANGE)
Distillates (petroleum), hydrotreated light	Xn R65 R66	265-149-8	64742-47-8	60 to 100%
Orange terpenes	Xn R65 Xi R38 R10 R52/53	232-433-8	8028-48-6	10 to 30%

Aerosol propelled by carbon dioxide

SECTION 4: FIRST AID MEASURES

Eye Contact: Flush immediately with water for 15 minutes, then seek medical attention.

Skin Contact: Wash skin with lots of water. Seek medical attention if any skin irritation persists.

Inhalation: Get fresh air and seek medical assistance if breathing is difficult.

Ingestion: DO NOT INDUCE VOMITING unless directed to do so by medical personal. Wash mouth with water, provide fresh air and seek immediate medical attention. Do not give anything by mouth if patient is unconscious.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media: Product is extremely flammable. Use foam, carbon dioxide or dry powder extinguisher.

Fire/Explosion Hazards: Extremely flammable aerosol, pressurised containers may explode in fire. Use water to keep fire exposed containers cool and disperse vapours. Solvent vapours may form explosive mixtures with air.

Decomposition Products: Exposure to fire may liberate carbon dioxide, carbon monoxide, hydrocarbon compounds and other unidentified thermal decomposition products from this product or its packaging.

Special Protective Equipment: Self contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Protection: Protective clothing, nitrile rubber gloves, chemical splash goggles. Extinguish all ignition sources - No smoking. Ensure adequate ventilation.

Containment and Disposal: Spills should be treated with dry, inert, absorbent, contained and disposed at legal waste disposal site. Area should be washed with detergent and water.

SECTION 7: HANDLING AND STORAGE

Handling Precautions: Wear nitrile rubber gloves and safety glasses when handling. Contaminated towels, etc. are combustible and should be soaked in water and detergent

solution immediately after use. Ensure adequate ventilation in enclosed areas. Do not smoke or spray on naked flame.

Storage Precautions: Store in ventilated area away from heat, direct sunlight and sources of ignition. Keep out of reach of children. Keep in original container. Do not expose to temperature exceeding 50°C. Do not puncture or incinerate even when empty.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits: Distillates (petroleum), hydrotreated light WEL-LTEL 1000mg/m³

Carbon dioxide WEL-LTEL 5000ppm WEL-STEL 15000ppm

Environmental Controls: For additional guidance, contact ENVIROWISE at www.envirowise.gov.uk or telephone 0800 585794

Eye Protection: Side shield safety glasses are recommended.

Protective Clothing: Standard work clothing and nitrile rubber gloves. Protective gloves should be inspected for wear before use and replaced regularly in accordance with the manufacturers specifications.

Respiratory Protection: Not required providing there is adequate ventilation and solvent vapours are below threshold limits. If excessive exposure cannot be avoided an approved organic solvent respirator should be used in well ventilated areas. Respirators should not be worn in confined spaces.

Ventilation: Ensure adequate ventilation to keep solvent vapour below threshold level.

Hygiene: Wash hands, clothing and towels after use or spill. Do not eat or drink when handling.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Colour/State: Aerosol colourless liquid

Odour: Citrus

pH Concentrate: Not applicable **pH Diluted:** Not applicable

Boiling Point / Range °C: 175-200

Flash Point °C: <21 **Method:** CC (Closed Cup)

Flammability Limit %: Not determined

Explosive Properties: Not applicable

Oxidising Properties: Not applicable

Vapour Pressure: Not determined

Relative Density (Water = 1): 0.775 **Solubility:** Not applicable

Partition Coefficient (N-octanol / Water): Not determined

Viscosity: Not applicable

Vapour Density: Not determined

Evaporation Rate: Not determined

% Active: 100

% Solids: Not applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Heat, flames and ignition sources.

Incompatibility (Materials to Avoid): Strong oxidising agents.

Hazardous Decomposition Products: Exposure to fire may liberate carbon dioxide, carbon monoxide, hydrocarbon compounds and other unidentified thermal decomposition products from this product or its packaging.

SECTION 11: TOXICOLOGICAL INFORMATION

Eye Contact: Liquid and vapour may cause mild irritation or discomfort.

Skin Contact: Repeated exposure may cause skin dryness or cracking.

Inhalation: High concentrations of vapour may cause dizziness, nausea and headache.

Ingestion: May cause irritation of mouth, respiratory tract and intestinal system.

Acute and Chronic Effects:

Acute Toxicity: Not established.

Corrosivity / Irritation: Skin, eye and respiratory.

Sensitisation: None known.

Repeated Dose Toxicity: Not established.

Mutagenicity: None

Carcinogenicity: None

Teratogenicity: None

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Product contains orange terpenes which is classified as Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Mobility: Not known.

Persistence and Degradability: Product contains orange terpenes which is classified as Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The major packaging materials of polyethylene and fibreboard are recyclable.

Bioaccumulative Potential: None known.

Other Effects: None known or no relevant data available for substances in this preparation.

SECTION 13: DISPOSAL CONSIDERATIONS

Do not puncture or incinerate even when empty. Do not discharge to drain or watercourse. Empty aerosols should be disposed of at legal waste disposal site. Aerosols are recyclable. See the free leaflet obtainable from the British Aerosol Manufacturers Association web-site www.bama.co.uk Contact local Environment Agency office for waste holder requirements.

SECTION 14: TRANSPORT INFORMATION

UN No: 1950

Classification: Flammable Gas

Proper Shipping Name: Aerosols

Packing Group: Special Requirements.

Road (ADR): Class 2. Classification code: 5F 'limited quantity'

Sea (IMDG): Class 2 'limited quantity'

SECTION 15: REGULATORY INFORMATION

Classification: EXTREMELY FLAMMABLE

Risk Phrases

R12 Extremely flammable.

R66 Repeated exposure may cause skin dryness or cracking.

Safety Phrases

S2 Keep out of the reach of children.

S9 Keep container in a well ventilated place.

S16 Keep away from sources of ignition – No Smoking.

S23 Do not breathe vapour/spray.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S35 This material and its container must be disposed of in a safe way.

S37 Wear suitable gloves.

S51 Use only in well ventilated areas.

The information given has been compiled with reference to the **CHEMICALS (HAZARD INFORMATION AND PACKAGING FOR SUPPLY) REGULATIONS (CHIP 4) 2009** (as amended), the **REGISTRATION, EVALUATION, AUTHORISATION AND RESTRICTION OF CHEMICALS (REACH) REGULATIONS** (as amended), the **CONTROL OF SUBSTANCES HAZARDOUS TO HEALTH REGULATIONS (COSHH) 2002** (as amended), **REGULATION (EC) NO. 648/2004 ON DETERGENTS** (as amended) and the **MANAGEMENT OF HEALTH AND SAFETY AT WORK REGULATIONS 1999** (as amended). This safety data sheet does not constitute the users own assessment of workplace risk as required by other health and safety regulations.

SECTION 16: OTHER INFORMATION

Risk Phrases for ingredients in section 3: R10 Flammable.

R38 Irritating to skin. R52 Harmful to aquatic organisms. R53

May cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking.

For additional information on safety, training and use of this product, contact the supplier. This product is intended for professional use only.

The information given is intended to be of assistance to users but is without guarantee. Variations can occur in application and users are advised to conduct their own tests. Suggestions for use neither give nor imply any guarantee as to the intended use.

Revisions: Replaces SDS A401 Issue / Revision Date 13/11/07 Revised Sections: 1, 2, 5, 6, 7, 8, 10, 14, 15, 16.